

# MERLIN SUNFLOWER AEROSOL

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 18/06/2015

Revision date: 26/11/2014

Version: 10.0

MERLIN SUNFLOWER AEROSOL

001.005

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : MERLIN SUNFLOWER AEROSOL  
Product code : 001.005  
Type of product : Aerosol  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use  
Industrial/Professional use spec : For professional use only  
Use of the substance/mixture : air freshener

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

OXFORD CITY SUPPLIES

UNIT 6 CENTREMEAD, OSNEY MEAD INDUSTRIAL EST, OXFORD, OX2 0ES, UNITED KINGDOM  
Tel: 01865 722 104 Fax: 01865 790 543 Email: sales@oxfordcitysupplies.com

#### 1.4. Emergency telephone number

Emergency number : Mon to Fri 8.30am to 5.00pm - 01865 722 104

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H222 - Extremely flammable aerosol  
H229 - Pressurised container: May burst if heated

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P211 - Do not spray on an open flame or other ignition source  
P251 - Do not pierce or burn, even after use  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

#### 2.3. Other hazards

No additional information available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane substance with national workplace exposure limit(s) (DK, IE)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	5 - 15	F+; R12	Flam. Gas 1, H220
butane substance with national workplace exposure limit(s) (DK, GB, IE)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	5 - 15	F+; R12	Flam. Gas 1, H220 Press. Gas
propan-2-ol, isopropyl alcohol, isopropanol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0 (REACH-no) 01-2119457558-25	1 - 5	F; R11 Xi; R36 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Full text of R- and H-phrases: see section 16

**SECTION 4: First aid measures****4.1. Description of first aid measures**

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of soap and water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms/injuries	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam.
------------------------------	-------------------------------------

**5.2. Special hazards arising from the substance or mixture**

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Explosion risk in case of fire.

**5.3. Advice for firefighters**

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
---------------------------	--

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

General measures	: Remove ignition sources.
------------------	----------------------------

**6.1.1. For non-emergency personnel**

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

**6.1.2. For emergency responders**

Protective equipment	: Use personal protective equipment as required.
----------------------	--

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

For containment	: Collect spillage.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

**6.4. Reference to other sections**

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use.
-----------------------------------	---

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Precautions for safe handling	: Do not spray on an open flame or other ignition source.
Hygiene measures	: Do not eat, drink or smoke when using this product.

**7.2. Conditions for safe storage, including any incompatibilities**

Technical measures	: Does not require any specific or particular technical measures.
Storage conditions	: Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Incompatible products	: Oxidizing agent. Strong acids. Strong bases.
Incompatible materials	: Direct sunlight. Heat sources. Sources of ignition.
Special rules on packaging	: Keep only in original container.

**7.3. Specific end use(s)**

No additional information available

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

<b>propane (74-98-6)</b>		
Denmark	Local name	Propan
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Ireland	Local name	Propane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	Notes (IE)	Asphx
<b>propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)</b>		
Denmark	Local name	Isopropylalkohol (2005)
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	490 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m <sup>3</sup> )	1000 mg/m <sup>3</sup>
Ireland	Local name	Isopropyl alcohol
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	Notes (IE)	Sk
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	650 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	0 mg/m <sup>3</sup>
United Kingdom	Local name	Propan-2-ol
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	999 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1250 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	500 ppm
<b>butane (106-97-8)</b>		
Denmark	Local name	n-Butan
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Ireland	Local name	Butane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	1450 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 8.2. Exposure controls

Materials for protective clothing	: Not required for normal conditions of use
Hand protection	: In case of repeated or prolonged contact wear gloves
Eye protection	: Not required for normal conditions of use
Skin and body protection	: Not required for normal conditions of use
Respiratory protection	: Not required for normal conditions of use

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Colourless.
Odour	: Floral.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0,81
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

**AIRFRESHENER - SUNFLOWERS**

Vaporizer	Aerosol
-----------	---------

**SECTION 12: Ecological information****12.1. Toxicity****propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

LC50 fishes 1	9640 mg/l
EC50 other aquatic organisms 1	13299 mg/l EC50 waterflea (48 h)
EC50 other aquatic organisms 2	> 1000 mg/l IC50 alga (72 h) mg/l

**12.2. Persistence and degradability**

No additional information available

**12.3. Bioaccumulative potential****propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

Log Pow	0,14
---------	------

**12.4. Mobility in soil**

No additional information available

**12.5. Results of PBT and vPvB assessment**

No additional information available

**12.6. Other adverse effects**

No additional information available

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Waste disposal recommendations : Do not pierce or burn, even after use.

**SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

**14.1. UN number**

UN-No. (ADR)	: 1950
UN-No. (IMDG)	: 1950
UN-No.(IATA)	: 1950

**14.2. UN proper shipping name**

Proper Shipping Name (ADR)	: AEROSOLS
Proper Shipping Name (IMDG)	: AEROSOLS
Proper Shipping Name (IATA)	: AEROSOLS, FLAMMABLE
Transport document description (ADR)	: UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG)	: UN 1950 AEROSOLS, 2.1

**14.3. Transport hazard class(es)****ADR**

Transport hazard class(es) (ADR)	: 2.1
Danger labels (ADR)	: 2.1



## Safety Data Sheet

according to Regulation (EC) No. 453/2010

**IMDG**

Transport hazard class(es) (IMDG) : 2.1  
 Danger labels (IMDG) : 2.1

**IATA**

Transport hazard class(es) (IATA) : 2.1  
 Hazard labels (IATA) : 2.1

**14.4. Packing group**

Packing group (ADR) : Not applicable  
 Packing group (IMDG) : Not applicable  
 Packing group (IATA) : Not applicable

**14.5. Environmental hazards**

Dangerous for the environment : No  
 Marine pollutant : No  
 Other information : No supplementary information available

**14.6. Special precautions for user****- Overland transport**

Classification code (ADR) : 5F  
 Special provisions (ADR) : 190, 327, 344, 625  
 Limited quantities (ADR) : 1L  
 Excepted quantities (ADR) : E0  
 Packing instructions (ADR) : P207, LP02  
 Special packing provisions (ADR) : PP87, RR6, L2  
 Mixed packing provisions (ADR) : MP9  
 Transport category (ADR) : 2  
 Special provisions for carriage - Packages (ADR) : V14  
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
 Special provisions for carriage - Operation (ADR) : S2  
 Tunnel restriction code (ADR) : D

**- Transport by sea**

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959  
 Limited quantities (IMDG) : SP277  
 Excepted quantities (IMDG) : E0  
 Packing instructions (IMDG) : P207, LP02  
 Special packing provisions (IMDG) : PP87, L2  
 EmS-No. (Fire) : F-D  
 EmS-No. (Spillage) : S-U  
 Stowage category (IMDG) : None

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

**- Air transport**

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

IBC code : Not applicable.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU-Regulations**

Contains no substances with Annex XVII restrictions  
 Contains no substance on the REACH candidate list  
 Contains no REACH Annex XIV substances

**15.1.2. National regulations****Germany**

VwVwS Annex reference : Water hazard class (WGK) 1, slightly hazardous to water (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

**Denmark**

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

**15.2. Chemical safety assessment**

No additional information available

**SECTION 16: Other information**

Full text of R-, H- and EUH-phrases:

Aerosol 1	Aerosol, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Press. Gas	Gases under pressure
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H229	Pressurised container: May burst if heated
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

SDS EU

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*