

SAFETY DATA SHEET

SHADES - VANILLA (MD)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SHADES - VANILLA (MD)
Product number KSD5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Air Freshener

1.3. Details of the supplier of the safety data sheet

Supplier **SELDEN RESEARCH LIMITED**
STADEN LANE
BUXTON
DERBYSHIRE
SK17 9RZ
UNITED KINGDOM

Tel. 01298 26226
Fax. 01298 26540
email safety@selden.co.uk

1.4. Emergency telephone number

National emergency telephone number Mon to Fri 8.30am to 5.00pm - 01298 26226

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Aerosol 1 - H222, H229

Health hazards

Eye Irrit. 2 - H319 Elicitation (Skin Sens.)

Environmental hazards

Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC)

F+;R12. R52/53.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains (L) Hexyl Cinnamyl, 1-(Hexahydrotetramethylmethanoazulenyl) ethan-1-one. May produce an allergic reaction.

Precautionary statements

SHADES - VANILLA (MD)

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P264 Wash hands thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|--|--|
| BUTANE | 30-60% |
| CAS number: 106-97-8 EC number: 203-448-7 | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Gas 1 - H220 | F+;R12 |
| Press. Gas, Liquefied - H280 | |
| PROPAN-2-OL | 10-30% |
| CAS number: 67-63-0 EC number: 200-661-7 | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 2 - H225 | F;R11 Xi;R36 R67 |
| Eye Irrit. 2 - H319 | |
| STOT SE 3 - H336 | |
| Ethylene brassylate | 1-5% |
| CAS number: 105-95-3 EC number: 203-347-8 | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Skin Irrit. 2 - H315 | N;R51/53. |
| Aquatic Chronic 2 - H411 | |
| (L) Hexyl Cinnamyl | <1% |
| CAS number: 101-86-0 EC number: 202-983-3 | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Skin Sens. 1 - H317 | Xi;R38. R43. |
| Skin Sens. 1 - H317 | |
| Aquatic Chronic 2 - H411 | |

SHADES - VANILLA (MD)

1-(Hexahydro-tetramethylmethanoazulenyl) ethan-1-one

<1%

CAS number: 32388-55-9 EC number: 251-020-3

M factor (Chronic) = 1

Classification

Skin Sens. 1B - H317

Aquatic Chronic 1 - H410

Classification (67/548/EEC or 1999/45/EC)

N;R50/53. R43.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion

Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention.

Skin contact

Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact

If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause chemical burns in mouth and throat. May cause stomach pain or vomiting.

Skin contact

Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact

Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters

SHADES - VANILLA (MD)

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions

Any spillage needs to be contained and not allowed to enter water courses

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

See product label for detailed usage and instructions.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment

**Eye/face protection**

Eye protection should be considered when changing aerosols in dispensing unit.

Hand protection

Hand protection not required.

Other skin and body protection

General workwear only

Hygiene measures

DO NOT SMOKE IN WORK AREA!

SECTION 9: Physical and Chemical Properties**9.1. Information on basic physical and chemical properties****Appearance**

Aerosol.

Colour

Colourless.

Odour

Characteristic. vanilla

Flash point

- 74°C

Upper/lower flammability or explosive limits

: 1.8

Relative density

<1 @ °C

Solubility(ies)

Soluble in water.

Auto-ignition temperature

+ 405°C

Comments

Information given relates to total aerosol container contents.

9.2. Other information**Other information**

None.

SECTION 10: Stability and reactivity**10.1. Reactivity**

May react with other cleaning chemicals. For specific reactions refer to Section 10.5

10.2. Chemical stability**Stability**

Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Not known.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting/explosion.

SHADES - VANILLA (MD)

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects

No toxicological data is available for this mixture, however data can be provided for specific raw materials upon request.

Inhalation

May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion

May cause burns in mucous membranes, throat, oesophagus and stomach. May cause stomach pain or vomiting.

Skin contact

Prolonged or repeated exposure may cause severe irritation. Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema.

Eye contact

Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity

Harmful to aquatic organisms. May cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Aquatic toxicity has not been carried out on this product. Data for raw materials contained in this product, when available, can be provided when necessary.

12.2. Persistence and degradability

Persistence and degradability

The product is biodegradable.

12.3. Bioaccumulative potential

The product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility

The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

SHADES - VANILLA (MD)

General Derogation for Limited Quantities may be applicable to appropriate pack sizes, please check relevant modal legislation.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS, FLAMMABLE

Proper shipping name (IMDG) AEROSOLS, FLAMMABLE

Proper shipping name (ICAO) AEROSOLS, FLAMMABLE

Proper shipping name (ADN) AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR/RID class 2

IMDG class 2.1

ICAO class/division 2.1

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Control of Substances Hazardous to Health Regulations 2002 (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

EU legislation

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical assessment has been carried out as this Safety Data Sheet is for a mixture.

SECTION 16: Other information

SHADES - VANILLA (MD)

General information

The following risk phrases relate to the raw materials in the product and not the product itself:-

Revision comments

Safety Data Sheet revised to be in accordance with EU Regulation No 453/2010 - REACH Regulations.

Revision date 28/04/2015

Revision 2

Risk phrases in full

R11 Highly flammable

R12 Extremely flammable.

R36 Irritating to eyes.

R38 Irritating to skin.

R43 May cause sensitisation by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

EUH208 Contains (L) Hexyl Cinnamyl, 1-(Hexahydrotetramethylmethanoazulenyl) ethan-1-one. May produce an allergic reaction.

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.